STANCE E+ 2



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Sport², 75Nm, powered by Yamaha
ECRAN	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
COMMANDE	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERIE	Giant EnergyPak 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible
CHARGEUR	Giant EnergyPak 4A smart charger compact, 60% charge in 2:00h
CADRE	
TAILLES	S, M, L, XL
COLORIS	Black Diamond
CADRE	ALUXX SL-grade aluminum, 1.5"~1.8" head tube,125mm travel FlexPoint suspension system, 'Boost' 148x12 UDH rear axle, EnergyPak Plus Range Extender Compatible
FOURCHE	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
AMORTISSEUR	SR Suntour Raidon R, 190x45mm, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Connect TR Riser 31.8x780mm
POIGNÉES	Giant Tactal single lock-on
POTENCE	Giant Contact
TIGE DE SELLE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLE	Giant Sport
PÉDALES	Aluminum Platform
DÉRAILLEUR	
MANETTES	Shimano Deore LinkGlide
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore LinkGlide, 10-speed
FREINS	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
LEVIERS DE FREIN	Tektro HD-M745 Orion
CASSETTE	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
CHAÎNE	Shimano, LinkGlide, CN-LG500
PÉDALIER	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29"
MOYEUX	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
RAYONS	Stainless Steel
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 29X2.40" WT Foldable, TLR, EXO, 60TPI [R]
EXTRAS	-
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
PORTE-BAGAGES	-
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 3 400,00 €

GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	400	425	450	475
Angle de tube de selle	76,0°	76,0°	76,0°	76,0°
Longueur du tube supérieur (mm)	580	607	639	671
Longueur du tube de direction (mm)	105	115	125	135
Angle du tube de direction	65,5°	65,5°	65,5°	65,5°
Déport de fourche (mm)	44	44	44	44
Trail (mm)	124	124	124	124
Empattement (mm)	1204	1233	1267	1301
Longueur des bases (mm)	468	468	468	468
Drop du boitier de pédalier (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Hauteur en statique (mm)	760	760	780	796
Largeur de cintre (mm)	780	780	780	780
Longueur de potence (mm)	40	40	50	50
Longueur des manivelles (mm)	165	165	165	165
Diamètre des roues	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.