TALON E+ EX



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Core, 50Nm, Powered by Yamaha, PedalPlus 6-sensor technology
ECRAN	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
COMMANDE	Giant RideControl Dash, high-angle visibility, full color LCD display
BATTERIE	Giant EnergyPak 500Wh, CO2 Neutral production
CHARGEUR	Giant EnergyPak 4A fast charger, 60% charge in 2:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL, XXL
COLORIS	Aged Denim
CADRE	ALUXX aluminum, Overdrive 1½ - 1⅛" head tube, integrated KSA18 kickstand mount
FOURCHE	SR Suntour XCM 32 ATB Coil NLO, 29" 100mm travel, Tapered 1½ - 1⅛" steerer
AMORTISSEUR	n/a
COMPOSANTS	
CINTRE	Giant Connect TR Riser 31.8x720~780mm (S: 720mm, M:750mm, L/XL/XXL: 780mm)
POIGNÉES	Giant Sole-O Grip
POTENCE	Giant Contact
TIGE DE SELLE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLE	Giant Sport
PÉDALES	Aluminum Platform
DÉRAILLEUR	
MANETTES	Shimano Altus
DÉRAILLEUR AVANT	n/a
DÉRAILLEUR ARRIÈRE	Shimano Alivio, 9-speed
FREINS	Tektro HD-M285, hydraulic disc, 180mm [F],160mm [R]
LEVIERS DE FREIN	Tektro HD-M285
CASSETTE	Shimano CS-HG200, 11-36T, 9-speed
CHAÎNE	KMC e.9 Sport, e-bike optimized
PÉDALIER	FSA Comet E-Bike crank arm set FSA MegaTooth Direct-mount 1X steel 36T
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant GX03V, 29er, Alluminum
MOYEUX	Giant eTracker Sport, [F] 9mm QR [R] 135mm QR
RAYONS	Stainless steel
PNEUS	Maxxis Rekon Race 29 x 2.25, Wire Bead, Dual Compound 60TPI
EXTRAS	KSA18 direct mount kickstand
ACCESSOIRES	
ECLAIRAGE	Herrmans H-BLACK MR4Axa BlueLine Steady E6 rear
PORTE-BAGAGES	Giant Rack-It MIK
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 2 550,00 €

GÉOMÉTRIE

CADRE	S	M	L	XL	XXL
Longueur de tube de selle (mm)	405	455	505	535	560
Angle de tube de selle	73,0°	73,0°	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	575	600	625	650	675
Longueur du tube de direction (mm)	105	115	125	140	155
Angle du tube de direction	68,0°	68,0°	68,0°	68,0°	68,0°
Déport de fourche (mm)	46	46	46	46	46
Trail (mm)	100,7	100,7	100,7	100,7	101
Empattement (mm)	1141	1167	1193	1219	1245
Longueur des bases (mm)	475	475	475	475	475
Drop du boitier de pédalier (mm)	45	45	45	45	45
Stack (mm)	625	634	643	657	671
Reach (mm)	384	406	428	449	470
Hauteur en statique (mm)	723	753	788	808	828
Largeur de cintre (mm)	690	750	750	780	780
Longueur de potence (mm)	50	60	60	70	70
Longueur des manivelles (mm)	160	165	170	170	170
Diamètre des roues	29"	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.